



ELECTRIC  
FAN

*ES – ESP – ESV230 NEO2*

## NEO TECHNOLOGY: AN OVAL JET FOR EVEN MORE EFFICIENT FANS

- A highly concentrated and ultra-powerful jet of air thanks to an optimal combination:
  - A very resistant propeller adapted to the power of the engine
  - A red one-piece double-walled reinforced shroud in high-density polyethylene
  - A high-tech grid made of composite material

## Adjustable from 1 to 6 m facing the opening without loss of power for:

- More space to manoeuvre at the entrance.
- Reduce noise levels inside the building.

## Tilt adjustment from -20° to +20°

- For an optimization of the orientation of the air jet facing a stoop.
- Pedal adjustment with integrated tilt indicator

## Wraparound protective frame

- With black and yellow textured epoxy coating

## Handy & stable

- Even in soft ground thanks to large wheels (200mm) very wide positioned at the back of the fan
- Higher manoeuvring handle for comfortable rolling

## Compact

- For easy storage in vehicle trunks

## Quick to implement

- Comes with a 2m cable and waterproof plug



## MULTI-APPLICATION

- Indoor and outdoor: Protected against splashing water (IP65)
- Alone, at the entrance of a building in VPP
- In VPP combined with other fans
- Blowing with ducts (optional)
- As a foam generator with its high expansion adapter (optional)
- As a misting device (option)



## CHARACTERISTICS

	ES 230-NEO2	ESP 230-NEO2	ESV 230-NEO2
References	I63-10-210N	I63-10-212N	I63-10-211N
Operation	Direct start	Soft starter	Variable speed drive
Open air flow		48,000 m <sup>3</sup> /h	
AMCA 240 flow rate		27,140 m <sup>3</sup> /h	
Compliance		CE	
Weight	≈37.8kg	≈38.5kg	≈39.5kg
Dimensions W x H x D		525 x 560 x 550 mm	
Propeller		420 mm	
T° of use		-20°C / +40°C	
Engine		2200 W	
Power supply	220V – 50 Hz - Single phase		220V – 50/60 Hz - single phase
Consumption (under established regime)	12.5 A	14 A	14 A
IP		IPX5	
Sound level		85.3 dB at 3m	
Type of ventilation		PPV	
Guarantees	Fan 5 years – Motor 3 years		

## OPTIONS - ACCESSORIES

50m extension in bag with lockable European plugs – cable 3 x 2.5 mm <sup>2</sup>	Ref. I63-00-030	Mister 1" BSP F	Ref. I60-20-204
Spiral blowing duct (5m - diam 430mm)	Ref. I60-20-252	V.BOX cube for vacuum-blowing kit	Ref. I63-20-217
High expansion foam adapter input 1.5" BSP M with 35m polyane duct	Ref. I60-20-105	5m duct for suction-blowing kit V BOX - Ø400mm	Ref. I63-20-014
Protective cover	Ref. I60-20-017	ZAG300 adapter for V-Box	Ref. I63-20-016

## REDUCED COST OF OWNERSHIP

Very low maintenance due to the very robust design and materials used.

ZF03.424.EN.3